









Прайс-лист оборудования RFID (Intermec) 2.10.08

	Наименование	Базовая конфигурация	Цена (евро) розничная
Считыватели			
	IF 30 Usage: Ethernet RFID Fixed reader with 4 mono-static RF ports for dock door and conveyor systems. (IF30A1230000012)	IF30, Std, NoRAD, None, 865MHz ETSI 302 208 1W	2300
	IF4B Intellitag RFID Serial Reader (IF4B002012)	IF4, 865MHz ETSI 302 208 1W (RoHS)	2400
	IF5U Intellitag RFID Fixed Reader reader with Ethernet, RS232 & connection to existing PLC/local controller base configurations. (851-067-002)	IF5, NoCAM, , None, 865MHz ETSI 302 208 1W	3300
	IF61A RFID Smart reader with Ethernet, RS232 & WiFi connectivity to existing host systems. (IF61A10100080312)	IF61A, 803, 865MHz ETSI 302-208, Wi-Fi	3250
Мобильные считыватели			
	IP30A Portable Reader	IP30A, BT, CN3/CN3E (*) 869MHz	1215
	IP4 Intellitag Portable Reader	IP4 Portable Reader, Circular Antenna, 869, ETSI 300 220 .5 W (RoHS)	1500

	751 Handheld Computer	Colour, 128MB RAM, 64MB ROM, Windows Mobile 2003 or WM 5, 802.11b/g WLAN radio option (must specify), Intermec Linear Imager (EV10)	2220
	CN3 Mobile computer	WM 5.0, 128MB RAM, 256MB ROM, SmartSystems™, QWERTY or Numeric Keypad options 802.11 b/g and Bluetooth, with a choice of a 2D Area Imager with scan handle support or 2.0 Megapixel Colour Camera, No GPS, No GPRS	2095
Оборудование для погрузчиков			
	IV7 Intellitag Vehicle Mount RFID Reader (IV7C202012)	Forklift Reader System 865MHz, ETSI 302 208 1W (RoHS)	2220
Принтеры			
	PM4i Thermal Transfer Printer (PM4C815300301120)	EasyCoder PM4i Thermal Transfer Printer with IM5 869MHz RFID Module resolution	3995
Антенны			
	IA39C	868, 8 dBic, Circular Polarisation, N	345

	IA36A	868, 6dBi, Vertical Polarisation, N	305
	IA39B	868, 10.5 dBic, Circular Polarisation, N RoHS	465
	IA33D	868, 6dBi, Circular Polarisation, N, ALBR, ETSI	345
	Antenna Cell	865-870Mhz 6W 8.5dBi RHCP, RoHS (IA33F, 86x, 8.5dBi, RHCP, N.	305
Тэги			
	RFID ID CARD	GEN 2, ETSI, BLANK	4,8 (до 99000)
	RFID ID CARD	GEN 2, ETSI, Magnetic Stripe	5,1 (до 99000)
	Large Rigid Tag	Gen 2, 1" x 6" form factor, singulated	5,9 (до 99000)
	Large Rigid Tag	ISO 18000-6B, 1" x 6" form factor, singulated	6,1 (до 99000)

	Small Rigid Tag	Gen 2, 1" x 3" form factor, singulated	4,8 (до 99000)
	Small Rigid Tag	ISO 18000-6B, 1" x 3" form factor, singulated	3,7 (до 99000)
	RFID Label	4"x6", 4"x2" EPC G2, Thermal Transfer	0,25 - 0,50