# AYC-Q64B

Anti-Vandal US Single Gang Backlit PROX + PIN Reader – Convertible



Part of the convertible line of readers/controllers, this unit can be operated as an outdoor backlit keypad and proximity reader that connects to any standard controller, or can convert into a fully featured, 500-user standalone controller when connected to Rosslare's PS-x25T family of intelligent power supply/relay units. This unit provides a most effective solution for indoor and outdoor access systems where PIN & proximity credentials are required. This attractive model features unique shiny blue illuminated metal keys on a metallic, epoxy filled, sealed housing.

### **GENERAL DESCRIPTION**

For greater peace of mind, this sturdy access control unit provides a rugged keypad with advanced access control features in an aesthetically-designed housing.

The AYC-Q64B offers programmable PIN & Proximity transmission formats, LED control and tamper detection, providing extra security and flexibility.

Come rain or shine, this unit can handle the challenge, with its extremely-strong metallic housing and waterproof enclosure for maximum durability.

The backlit keypad, with its auto-dimming options, is clearly visible day or night, making these units ideal for residential and commercial applications.

#### **MAIN FEATURES**

- Supports 4- to 8-digit PIN credentials and 125 kHz EM type RFID cards and tags
- Smooth, attractive design, with all-weather indoor and outdoor operation
- Large, highly-visible blue backlit keypad

- 2 tri-colored LEDs and an integral sounder for programming and operation
- User friendly menu, based on keypad, LED and sounder indicators
- Back and cover optical tamper detection and output
- Default operation as a multi-format reader (Wiegand 26-Bit/Clock & Data)
- Automatically recognizes Rosslare's PS-x25T intelligent power supply family converting it into a 500-user standalone controller with secure relays

#### PROFESSIONAL GRADE FEATURES

- 8 selectable PIN transmission modes including options for Key Stream, Binary, Parity, and 3x4 Matrix
- Supports Wiegand or Clock & Data transmission formats
- Comes with a mounting and drilling label, security screw, and tool set to prevent unauthorized opening
- 60 cm (23.6 in.) shielded interface cable



# **SPECIFICATIONS**

## **ELECTRICAL SPECIFICATIONS**

| Operating Voltage Range      | Reader mode: 5 to 16 VDC from a standard controller<br>Controller mode: PS-x25T series intelligent power supplies   |
|------------------------------|---|
| ■ Input Current              | Standby: 90 mA at 12 VDC<br>Maximum: 130 mA at 16 VDC   |
| ■ Proximity Card Reader      | Maximum read range*: 45 mm (1.8 in.)  Modulation: ASK at 125 kHz  Compatible cards: All 26-Bit EM cards  * Measured using Rosslare Prox Card AT-R14 or equivalent. Range also depends on electrical environment and proximity to metal. |
| ■ Tamper                     | Optical back tamper sensor, O.C. active low, 32 mA max. sink current  |
| OPERATIONAL SPECIFICATIONS   |   |
| Keypad                       | 3x4 keys for local programming and 4- to 8-digit PIN codes entry  |
| <ul><li>Design</li></ul>     | Epoxy potted, fully-sealed in a rugged metal enclosure, blue backlit metal keys, highly strong construction. Suitable for extremely harsh environments.   |
| ■ Audio/Visual               | Two tri-color LED indicators, built-in buzzer   |
| READER MODE                  |   |
| ■ LED Control                | Dry contact, N.O.   |
| Facility Code                | Programmable  |
| Read Card Format             | Selectable Wiegand 26-Bit or Clock & Data   |
| ■ PIN Code Formats           | 8 selectable formats, from 1- to 8-digit length PIN codes   |
| CONTROLLER MODE              | (available with PS-x25T series intelligent power supplies only)   |
| Capacity                     | 500 users, dual code/card or code + card each   |
| User Levels                  | Normal, Secure, Master  |
| Security Modes               | Normal, Bypass, Secure  |
| Outputs                      | Lock Strike output<br>Auxiliary output (PS-x25T series)   |
| Inputs                       | REX (Request-to-Exit) Auxiliary/door monitor with 10 programmable modes   |
| ENVIRONMENTAL SPECIFICATIONS |   |
| Operating Environment        | All weather, indoor and outdoor use, meets IP65   |
| Operating Temperature Range  | -35°C to 66°C (-31°F to 151°F)  |
| Operating Humidity Range     | 0 to 95%  |
| PHYSICAL SPECIFICATIONS      |   |
| Dimensions                   | 120 x 76 x 21 mm (4.7 x 3 x 0.8 in.)  |
| Weight                       | 480 g (1.1 lb)  |
| SYSTEM COMPONENTS            | AYC-Q64B is compatible with standard access controllers in Reader mode. With Rosslare's PS-x25T intelligent power supply series it automatically converts into a 500-user secure controller.  |
| PRODUCT WARRANTY             | 5-year limited product warranty   |

#### **ABOUT ROSSLARE SECURITY**

Rosslare Security Products, a division of Rosslare Enterprises Ltd., has been manufacturing high-quality security products since 1980. The company's three main lines – Access Control, Intrusion Detection and Guard Patrol – together with a growing product range have transformed Rosslare Security into a major worldwide force in security. Rosslare holds itself to the highest standards of customer service and manufacturing (ISO 9001:2008, ISO 14001:2004, ISO 13485:2003). The company complies with the EU Directive 2002/95/EC on Restriction of Hazardous Substances (RoHS).

www.rosslaresecurity.com











